

# MATERIAL SAFETY DATA SHEET

5555  
01 00

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

5555

HMIS CODES

Health	2
Flammability	0
Reactivity	0

PRODUCT NAME

MINWAX\* POLYCRYLIC\* Gloss Protective Finish, Clear

MANUFACTURER'S NAME

MINWAX Company  
10 Mountainview Road  
Upper Saddle River, NJ 07458

EMERGENCY TELEPHONE NO.

(216) 566-2917

DATE OF PREPARATION

16-MAY-03

INFORMATION TELEPHONE NO.

(800) 523-9299

## Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
1	34590-94-8	2-Methoxymethylethoxypropanol		
		ACGIH TLV	100 ppm (skin)	0.4 mm
		ACGIH TLV	150 ppm (skin) STEL	
		OSHA PEL	100 ppm (skin)	
		OSHA PEL	150 ppm (skin) STEL	
2	29911-28-2	1-(2-Butoxymethylethoxy)-propanol		
		ACGIH TLV	Not Available	0.06 mm
		OSHA PEL	Not Available	
4	5131-66-8	Butoxypropanol		
		ACGIH TLV	Not Available	0.6 mm
		OSHA PEL	Not Available	
3	107-21-1	Ethylene Glycol		
		ACGIH TLV	50 ppm CEILING	0.12 mm
		OSHA PEL	50 ppm CEILING	
1	9014-85-1	Decylpoly(ethyleneoxy)ethanol		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
2	872-50-4	1-Methyl-2-Pyrrolidone		
		ACGIH TLV	Not Available	1 mm
		OSHA PEL	Not Available	

## Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Continued on page 2

## =====

SIGNS AND SYMPTOMS OF OVEREXPOSURE  
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

## CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

## =====

## Section 4 -- FIRST AID MEASURES

-----

If INHALED:	If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN:	Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
If in EYES:	Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED:	Do not induce vomiting. Get medical attention immediately.

=====

## Section 5 -- FIRE FIGHTING MEASURES

-----

FLASH POINT	LEL	UEL
>200 F PMCC	N.A.	N.A.

## FLAMMABILITY CLASSIFICATION

Not Applicable

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## =====

## Section 6 -- ACCIDENTAL RELEASE MEASURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

## =====

## Section 7 -- HANDLING AND STORAGE

## STORAGE CATEGORY

DOL Storage Class IIIB

=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

=====

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

-----

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## =====

## Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT 8.51 lb/gal 1020 g/l  
SPECIFIC GRAVITY 1.02  
BOILING POINT 212 - 449 F 100 - 231 C  
MELTING POINT Not Available  
VOLATILE VOLUME 71 %  
EVAPORATION RATE Slower than ether  
VAPOR DENSITY Heavier than air  
SOLUBILITY IN WATER N.A.  
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)  
2.52 lb/gal 302 g/l Less Water and Federally Exempt Solvents  
1.05 lb/gal 126 g/l Emitted VOC

## =====

## Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable  
CONDITIONS TO AVOID  
None known.  
INCOMPATIBILITY  
None known.  
HAZARDOUS DECOMPOSITION PRODUCTS  
By fire: Carbon Dioxide, Carbon Monoxide  
HAZARDOUS POLYMERIZATION  
Will not occur

## =====

## Section 11 -- TOXICOLOGICAL INFORMATION

## -----

## CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.  
Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

## -----

## TOXICOLOGY DATA

CAS No.	Ingredient Name				
34590-94-8	2-Methoxymethylethoxypropanol				
		LC50	RAT	4HR	Not Available
		LD50	RAT		5135 mg/kg
29911-28-2	1-(2-Butoxymethylethoxy)-propanol				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
5131-66-8	Butoxypropanol				
		LC50	RAT	4HR	Not Available
		LD50	RAT		1900 mg/kg
107-21-1	Ethylene Glycol				
		LC50	RAT	4HR	Not Available
		LD50	RAT		4700 mg/kg
9014-85-1	Decylpoly(ethyleneoxy)ethanol				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
872-50-4	1-Methyl-2-Pyrrolidone				
		LC50	RAT	4HR	Not Available
		LD50	RAT		4200 mg/kg

#### Section 12 -- ECOLOGICAL INFORMATION

##### ECOTOXICOLOGICAL INFORMATION

No data available.

#### Section 13 -- DISPOSAL CONSIDERATIONS

##### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

#### Section 14 -- TRANSPORT INFORMATION

No data available.

#### Section 15 -- REGULATORY INFORMATION

##### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol	3	
872-50-4	1-Methyl-2-Pyrrolidone	2	

##### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## =====

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing,  
on the TSCA Inventory.

## =====

Section 16 -- OTHER INFORMATION

-----

This product has been classified in accordance with the hazard criteria  
of the CPR and the MSDS contains all of the information required by the  
CPR.

The above information pertains to this product as currently formulated,  
and is based on the information available at this time. Addition of  
reducers or other additives to this product may substantially alter the  
composition and hazards of the product. Since conditions of use are  
outside our control, we make no warranties, express or implied, and assume  
no liability in connection with any use of this information.